

# TRU JET

# DTF F2

- Soft touch
- Flexible
- Vivid color
- Unlimited color opportunity
- Instant proofing



**TRU JET**  
Digital Inks

  
**SAKURA**  
Digital Sublimation Ink

**inēdit**  
neoStampa

**CALDERA**



**ergosoft**  
rip solutions



**PM TEX**  
Poland

“PM TEX” Sp. z o.o.  
ul. Wojskowa 5/90, 60-792 Poznań, Polska.  
NIP 7792533536, KRS 0000939461  
Tel: +48 571 480 510

[WWW.TRUJETPRINT.PL](http://WWW.TRUJETPRINT.PL)  
[info@trujetprint.pl](mailto:info@trujetprint.pl)  
f @ d /TruJetPrint

# TRU JET

# FFE

## TECHNICAL PARAMETERS

Maximum Printing Width	600 mm
Print Head	Two heads EPSON i3200 print head One head for color ink, one head for CMYK
Printing Method	White layer over colored layer
Ink	Pigment ink for PET film
Print Speed	6Pass - 8m <sup>2</sup> / h
RIP Software	TexPrint, Neostampa, MainTop
Printer Equipment	Recirculation pump for white ink
Powdering Equipment	Powder shake control powder and amount control
Drying Equipment	Front heat plate, dry fixation, cold fans
Environment	Temperature :20-30°C Humidity :45% - 65%
Power Specifications	Printer :230W Powdering Machine :3kW - 6kW
Product Dimensions <small>(WxDxH)</small>	Printer :1660 x 830 x 1570 cm Accessories :2306 x 1092 x 1102 cm
Net / Gross Weight	Printer 152 kg / 180 kg Powdering Machine 210 kg / 300 kg



**PM TEX**  
Poland

“PM TEX” Sp. z o.o.  
ul. Wojskowa 5/90, 60-792 Poznań, Polska.  
NIP 7792533536, KRS 0000939461  
Tel: +48 571 480 510

[WWW.TRUJETPRINT.PL](http://WWW.TRUJETPRINT.PL)  
[info@trujetprint.pl](mailto:info@trujetprint.pl)  
 /TruJetPrint