

## HIGH PERFORMANCE SOLUTIONS

**M16** **32**

- 750 m<sup>2</sup>/h printing speed
- 320 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.16 printheads
- Very precise printing, perfectly clear output
- Robust Structure

### Printing Speed

**750** m<sup>2</sup>/h



### Printing Width

**320** cm width



**TRUJET**  
DIGITAL PRINTING SOLUTIONS

  
**SAKURA**  
Digital Sublimation Ink

**inēdit**  
neoStampa

**CALDERA**



**ergosoft**  
rip solutions



**PM TEX**  
Poland

“PM TEX” Sp. z o.o.  
ul. Wojskowa 5/90, 60-792 Poznań, Polska.  
NIP 7792533536, KRS 0000939461  
Tel: +48 571 480 510

[WWW.TRUJETPRINT.PL](http://WWW.TRUJETPRINT.PL)  
[info@trujetprint.pl](mailto:info@trujetprint.pl)  
    /TruJetPrint



- Mimimum drop size 2 pl
- n.16 staggered epson i3200 printhead
- n.3200 nozzles per head, n.51200 nozzles in total

- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean




- Pneumatic shafts are used paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding

- Independent pump for each print head group
- Independent cleaning pump for wiper & flashing stage.



- Continuous pinch roller design to prevent uneven paper.
- Patented paper suction system with diagonal channels

- Special design patented 2 stage ink feeding system



## TECHICAL PROPERTIES

Print Head	n.16 i3200 On demand Piezo print head
Maximum Print Width	3200 mm
Ink Type	Dye Sublimation
Number of Colors	4 Colors, 6-8 Colors (Optional)
Ink Feeding System	Big Ink Tank (25L / Tank) System
Media	Width: 210 ~ 3150 mm Thickness: 1 mm or less Weight: up to 250 kg Lenght: 400 - 500 m Roll Diameter: 50 - 75 mm
Printing Speeds	360 x 1200 dpi - 2 pass 750 m <sup>2</sup> /h 720 x 1200 dpi - 4 pass 375 m <sup>2</sup> /h
RIP Software	ErgoRIP (textprint) / Neostampa / Maintop
Interface	Gigabit Ethernet
Power Features	AC 100 ~ 120 V ± 10 / AC 220 ~ 240 V ± 10, 50/60 Hz + 1Hz
Power Consumption	Total: 16,7 kW
Net Sizes (G x D x Y)	5000 x 1700 x 3200mm (G x D x Y)
Gross Sizes (G x D x Y)	5450 x 1890 x 3455mm (G x D x Y)
Net / Gross Weight	1000 kg / 1100 kg