

TRUJET

DIGITAL PRINTING SOLUTIONS

FT4

- Soft touch
- Flexible
- Vivid color
- Unlimited color opportunity
- Instant proofing



TRUJET
DIGITAL PRINTING SOLUTIONS


SAKURA
Digital Sublimation Ink

inēdit
neoStampa

CALDERA



ergosoft
rip solutions



PM TEX
Poland

“PM TEX” Sp. z o.o.
ul. Wojskowa 5/90, 60-792 Poznań, Polska.
NIP 7792533536, KRS 0000939461
Tel: +48 571 480 510

WWW.TRUJETPRINT.PL
info@trujetprint.pl
 /TruJetPrint

FF4

TECHNICAL PARAMETERS

| | |
|---|--|
| Maximum Printing Width | 600 mm |
| Print Head | Four heads EPSON i3200 print head Two heads for color ink, two heads for CMYK |
| Printing Method | White layer over colored layer |
| Ink | Pigment ink for PET film |
| Print Speed | 6 Pass -14m ² / h |
| RIP Software | TexPrint, Neostampa, MainTop |
| Printer Equipment | Recirculation pump for white ink |
| Powdering Equipment | Powder shake control powder and amount control |
| Drying Equipment | Front heat plate, dry fixation, cold fans |
| Environment | Temperature :20-30°C Humidity :45% - 65% |
| Power Specifications | Printer :230W Powdering Machine :3kW - 6kW |
| Product Dimensions <small>(WxDxH)</small> | Printer :1660 x 830 x 1570 cm Accessories :2306 x 1092 x 1102 cm |
| Net / Gross Weight | Printer 152 kg / 180 kg Powdering Machine 210 kg / 300 kg |

