

HIGH PERFORMANCE SOLUTIONS

M8²⁶

- 374 m²/h printing speed
- 260 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.8 printheads
- Very precise printing, perfectly clear output
- Robust Structure



Printing Speed

374 m²/h

Printing Width

260 cm width



- Minimum drop size 2 pl
- n.8 staggered Epson i3200 printhead
- n.3200 nozzles per head, n.25600 nozzles in total

- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean



- Pneumatic shafts are used for paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding

- Independent pump for each print head group
- Independent cleaning pump for wiper & flashing stage.



- Continuous pinch roller design to prevent uneven paper.
- Patented paper suction system with diagonal channels

- Special design patented 2 stage ink feeding system



TECHICAL PROPERTIES

Print Head	n.8 i3200 On demand Piezo print head / Staggered
Maximum Print Width	2750 mm
Ink Type	CMYK, Dye Sublimation
Number of Colors	4 Colors
Ink Feeding System	* 5 lt / color opened ink feeding system (filter system) * 11 lt / color Jumbo ink system (filter, sub-tank, level & error sensor) (optional)
Media	Width: 210 ~ 2750 mm Thickness: 1 mm or less Weight: up to 200 kg Length: 400 - 500 m Roll Diameter: 300 mm
Printing Speeds	360 x 1200 dpi - 2 pass 374 m ² /h 720 x 1200 dpi - 4 pass 187 m ² /h
RIP Software	ErgoRIP (textprint) / Neostampa / Maintop
Interface	Gigabit Ethernet
Power Features	AC 100 ~ 120 V, 2.8A (600W) / AC 220 ~ 240 V, 1.5A (600W) Heater: 1,5 kW for each lamp
Power Consumption	300 W or less (except drying unit)
Net Sizes (G x D x Y)	4360 x 1660 x 1700mm (G x D x Y)
Gross Sizes (G x D x Y)	4300 x 1600 x 1650mm (G x D x Y)
Net / Gross Weight	750 kg / 930 kg